

M/T “KEREM KA”

Chemical and Oil Tanker



UNI-CHARTERING

M/T Kerem Ka

Type of vessel Tanker for oil and chemicals, type 2, I+HULL+MACH, UNRESTRICTED NAVIGATION , OIL/CHEMICAL TANKER ESP , TYPE 2, +AUT-UMS+I.G

Built 2009 at Selay Shipyard, Istanbul
Flag Turkish
Call sign TCWP5
Class B.V

Particulars

LOA	121,62	m
LPP	112,31	m
Parallel body, loaded	70	m
Breath moulded	16	m
Height from keel to mast	34.43	m
Depth moulded	8	m
Draft summer	6,33	m
Draft ballast	4,25	m
TPC	16.431	mt
Airdraft in ballast / loaded condition	28,454 m / 22,25	m
Size of manifolds	2 x 10pcs. - 6 inches	
Distance from bow to centre manifold	65,197	m
Distance from stern to centre manifold	56,4	m
Distance between manifolds	410	mm
Distance from ship side to manifold	3,24	m
Distance from deck to manifold	1,57	m
Cargo tank capacity	7074,3	m3 (98%)
Slop tank capacity	139,3	m3 (98%)
Ballast tank capacity	2795	m3

Deadweight 6,266 metric tonnes
Tonnage international Gross 4,236 / Net 2,039
Coating Marineline
Bowthruster 1 pc. bowthruster, 350 kW
Auxiliary engines 3 x 450 K.W Cat
Speed / consumption 11 knts. On abt. 10 mts HFO pr. day
Cranes 1 x 5t swl hose crane
Cargo pumps 12* 200 m3/h.- Marflex Deepwell

Ballasting / Deballasting during load / disch
Ballast pumps 2 pumps each 150 m3/h.
No. of cargo tanks 12 cargo + 2 slop
No. of segregations 12